


The Superflat bathroom drain glued flange, DN 50, tileable



Article information

Item no.: 42701.95
GTIN: 4026092029664
Price group: 10

Advantages

- Movable outlet socket
- Lip seal fixed on the drain body
- Side inlet via odour trap

Description

The Superflat bathroom drain is suitable for indoor floor drainage. The drain made of PP is equipped with a secure, reliably installed seal as well as a removable odour trap.

Variant

Sealing water height: 30 mm
Discharge rate (l/s) with 20 mm backwater: 0,8

General characteristics

Nominal size (DN): 50
Outer diameter (OD): 50 mm

Dimensions

Vertical adjustment: 25 - 90 mm
Net weight: 0,93 kg
Gross weight: 1,17 kg
Cutout dimension, width: 350 mm
Cutout dimension, length: 350 mm
Vertical adjustment: vertically adjustable upper section
Length: 332 mm
Width: 332 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Number of outlets: 1
Inlet nominal size (DN): 40 mm
Inlet type: 1
Material of drain body: PP

Coverage features

Type of cover:	tileable cover plate
Cover material:	tileable
Colour of cover:	selectable
Width of cover:	110 mm
Length of cover:	110 mm
Frame material:	Stainless steel 14301
Cover locking:	placed
Load class:	K 3 (EN 1253-1)
Rim length:	110 mm
Rim material:	110 mm
Upper section material:	PP
Odour trap:	included