

Grease separat. EasyClean Modular free, NS 1, Standard, 2-part



Article information

Item no.: 93001

GTIN: 4026092030875

Price group: 60

Advantages

- Ideal where access is tight
- can be divided into several parts for insertion, for an insertion opening of max. 66 cm
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. Thanks to the modular design, the separator can be inserted even where access is extremely tight. The collecting tank (NS 0.5 with two tanks) made of permanently resistant polymer (PE) is equipped with an integrated sludge trap. A service access cover with odour-tight cover and quick-release closures makes easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant

Sound absorption mat: two-piece chamber

Disposal variant: Standard

Protection class motor:

Sludge bucket:

Nominal size (NS):

SonicControl:

Refill inlet in accordance with DIN 1988:

no

Type of disposal: manual with suction hose

General characteristics

Material: PE

Installation situation: free-standing installation

Delivery state: Installation-ready (connection parts must be

connected on site)

Dimensions

Net weight: 41,5 kg
Gross weight: 51 kg
Height tank bottom up to centre section: 648 mm
Height centre section to top edge of tank: 340 mm



Set-up area, length:

Set-up area, width:

Set-up area, height:

Packaging dimension:

Tank/drain body

Distance pipe bottom outlet to tank bottom:

Distance pipe bottom inlet to tank bottom:

Outlet nominal size (OD):

Outlet nominal size (DN):

Inlet nominal size (DN):

110 mm

Inlet nominal size (DN):

110 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes

in accordance with DIN 19560, PP or AS

Coverage features

Type of cover: Cover Cover material: Polymer Colour of cover: black

Cover locking: Quick-release closure

Tightness: odour-tight

Wastewater contents

Separator contents: 100 l
Total volume: 200 l
Hose: 100 l
Storage quantity of light liquid: 40 l

Control

Control unit: no